49F/49FA Sockets

RELAY SOCKETS




- The dielectric strength can reach 2000VAC and the insulation resistance is $1000M\Omega$
- Ensure secure retention of relays
- Components available: Removal tool
- Applicable relay types: HF49FD
- Environmental friendly product (RoHS compliant)

CHARACTERISTICS

Туре	Nominal Voltage	Nominal Current	Ambient Temperature	Dielectric Strength min.
49F/49FA	250VAC	7A	-40 °C to 70°C	2000VAC

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT Unit: mm

Components Socket **Outline Dimensions PCB** Layout Available 49F removal tool 49F-B (Top View) PCB terminal, PCB mounting Applicable for (Top View) HF49FD 1 type 49FA removal tool 49F-B (Top View) PCB terminal, PCB mounting (Top View) Applicable for HF49FD 2 type




2012 Rev. 1.02

DIMENSION OF RELATED COMPONENT (AVAILABLE)

Unit: mm

Removal Tool





Things to be noticed when selecting sockets:

- 1. Please choose suitable relay socket according to the actual mounting environment, relay contact poles and terminal layout. If there is any query on selection, please contact Hongfa for the technical service.
- As for related components, they should be selected separately. Please do give clear indication of the types of relay sockets and related components you choose while placing order.

Disclaimer

This datasheet is for the customers' reference. All the specifications are subject to change without notice.

We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.