


# CHIP TYPE

# CA Series

Предлагаем ЭЛЕКТРОННЫЕ КОМПОНЕНТЫ  
(радиодетали) СО СКЛАДА И ПОД ЗАКАЗ  
Беларусь г.Минск тел./факс 8(017)200-56-46  
www.fotorele.net e:mail minsk17@tut.by  
Surface-Mounted Device

JAMICON®

- Height : 5.4mm.
- Load life : 85°C 2000 hours.
- Low leakage current (0.5  $\mu\text{A}$  to 2.0  $\mu\text{A}$  max.)



## SPECIFICATION

Item	Characteristic							
Operation Temperature Range	-40 ~ +85°C							
Rated Working Voltage	6.3 ~ 50VDC							
Capacitance Tolerance (120Hz 20°C)	±20%(M)							
Leakage Current (20°C)	$I \leq 0.002CV$ or 0.5 ( $\mu\text{A}$ )				I : Leakage Current ( $\mu\text{A}$ )			
	*Whichever is greater after 2 minutes				C : Rated Capacitance ( $\mu\text{F}$ ) V : Working Voltage (V)			
Surge Voltage (20°C)	W.V.	6.3	10	16	25	35	50	
	S.V.	8	13	20	32	44	63	
Dissipation Factor (tan $\delta$ ) (120Hz 20°C)	W.V.	6.3	10	16	25	35	50	
	tan $\delta\phi$	0.24	0.20	0.16	0.14	0.12	0.10	
Low Temperature Stability	Impedance ratio at 120Hz							
	Rated Voltage (V)	6.3	10	16	25	35	50	
	-25°C / +20°C	4	3	2	2	2	2	
	-40°C / +20°C	8	6	4	4	3	3	
Load Life	After 2000 hours application of W.V. and +85°C ripple current value, the capacitor shall meet the following limits. (DC + ripple peak voltage $\leq$ rate working voltage)							
	Capacitance Change	$\leq \pm 25\%$ of initial value						
	Dissipation Factor	$\leq 200\%$ of initial specified value						
	Leakage current	$\leq$ initial specified value						
Shelf Life	At +85°C, no voltage application after 1000 hours, the capacitor shall meet the limits for load life characteristics. (With voltage treatment)							
Resistance to Soldering Heat	Capacitors placed on a 250°C hot plate for 30 seconds with their electrode terminals facing downward will fulfill the following conditions after being cooled to room temperature.							
	Capacitance Change	$\leq \pm 10\%$ of initial value						
	Dissipation Factor	$\leq$ initial specified value						
	Leakage current	$\leq$ initial specified value						

## DIMENSIONS (mm)

D	L	A	H	I	W	P	K
4.0	5.4	4.3	5.5MAX	1.8	0.65±0.1	1.0	0.35 <sup>+0.15</sup> <sub>-0.20</sub>
5.0	5.4	5.3	6.5MAX	2.2	0.65±0.1	1.5	0.35 <sup>+0.15</sup> <sub>-0.20</sub>
6.3	5.4	6.6	7.8MAX	2.6	0.65±0.1	2.1	0.35 <sup>+0.15</sup> <sub>-0.20</sub>

