



HF141FF


MINIATURE HIGH POWER RELAY



File No.:E133481



File No.:CQC09002034351



Features

- 10A switching capability
- 5kV dielectric strength (between coil and contacts)
- Sockets available
- 1 Form A ,1 Form B and 1 Form C configurations
- Plastic sealed and flux proofed types available
- Environmental friendly product (RoHS compliant)
- Outline Dimensions: (29.0 x 12.6 x 20.6) mm

CONTACT DATA		
Contact arrangement	1A, 1B, 1C	
Contact resistance	50mΩ max.(at 1A 6VDC)	
Contact material	AgSnO <sub>2</sub> , AgCdO	
Contact rating (Res.load)	Standard	High Capacity
	8A 250VAC /30VDC 10A 125VAC	10A 30VDC 10A 250VAC
Max. switching power	2000VA / 240W	2500VA / 300W
Max. switching current	10A	
Max. switching voltage	250VAC / 30VDC	
Mechanical endurance	1 x 10 <sup>7</sup> OPS	
Electrical endurance	1 x 10 <sup>5</sup> OPS	

CHARACTERISTICS		
Insulation resistance		1000MΩ (at 500VDC)
Dielectric strength	Between coil & contacts	5000VAC 1min
	Between open contacts	1000VAC 1min
Operate time (at nomi. volt.)		15ms max.
Release time (at nomi. volt.)		5ms max.
Vibration resistance		10Hz to 55Hz 1.5mm DA
Shock resistance	Functional	98m/s <sup>2</sup>
	Destructive	980m/s <sup>2</sup>
Humidity		5% to 85% RH
Ambient temperature		-40°C to 70°C
Termination		PCB
Unit weight		Approx. 13g
Construction		Plastic sealed, Flux proofed

Notes: 1) The data shown above are initial values.  
2) Please find coil temperature curve in the characteristic curves below.  
3) UL insulation system: Class A

COIL	
Coil power	Standard: Approx. 720mW; Sensitive: Approx. 550mW

COIL DATA					at 23°C
Standard type					
Nominal Voltage VDC	Pick-up Voltage VDC max.	Drop-out Voltage VDC min.	Max. Allowable Voltage VDC	Coil Resistance Ω	
5	4.0	0.5	6.5	36 x (1±10%)	
6	4.8	0.6	7.8	50 x (1±10%)	
9	7.2	0.9	11.7	115 x (1±10%)	
12	9.6	1.2	15.6	200 x (1±10%)	
18	14.4	1.8	23.4	460 x (1±10%)	
24	19.2	2.4	31.2	820 x (1±10%)	
48	38.4	4.8	62.4	3300 x (1±10%)	

Sensitive type				
Nominal Voltage VDC	Pick-up Voltage VDC max.	Drop-out Voltage VDC min.	Max. Allowable Voltage VDC	Coil Resistance Ω
5	4.0	0.5	6.5	47 x (1±10%)
6	4.8	0.6	7.8	68 x (1±10%)
9	7.2	0.9	11.7	155 x (1±10%)
12	9.6	1.2	15.6	270 x (1±10%)
18	14.4	1.8	23.4	620 x (1±10%)
24	19.2	2.4	31.2	1100 x (1±10%)
48	38.4	4.8	62.4	4400 x (1±10%)

Notes: When requiring pick-up voltage < 80% of nominal voltage, special order allowed.

SAFETY APPROVAL RATINGS

UL/CUL	High Capacity	10A 30VDC/250VAC
	Standard	8A 30VDC/250VAC
		10A 125VAC

Notes: Only some typical ratings are listed above. If more details are required, please contact us.

ORDERING INFORMATION


	HF141FF /			012	-H	S	P	G	(XXX)
Type									
Coil voltage	5, 6, 9, 12, 18, 24, 48VDC								
Contact arrangement	H:1 Form A      D:1 Form B      Z:1 Form C								
Construction <sup>1)</sup>	S: Plastic sealed      Nil: Flux proofed								
Coil power	P: Standard      Nil: Sensitive								
Contact capacity	G: High capacity (AgSnO2)      Nil: Standard type (AgCdO)								
Customer special code									

Notes: 1) Under the ambience with dangerous gas like H<sub>2</sub>S, SO<sub>2</sub> or NO<sub>2</sub>, plastic sealed type is recommended; Please test the relay in real applications.  
If the ambience allows, flux proofed type is preferentially recommended.  
If water cleaning is required after the relay is assembled on PCB, please contact us for suggestion about suitable parts.

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT

Unit: mm

Outline Dimensions






Remark: 1) In case of no tolerance shown in outline dimension: outline dimension ≤1mm, tolerance should be ±0.2mm; outline dimension >1mm and ≤5mm, tolerance should be ±0.3mm; outline dimension >5mm, tolerance should be ±0.4mm.  
2) The tolerance without indicating for PCB layout is always ±0.1mm.

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT


Unit: mm

PCB Layout (Bottom view)




Remark: The width of the gridding is 2.5mm.

Wiring Diagram (Bottom view)




CHARACTERISTIC CURVES


MAXIMUM SWITCHING POWER



ENDURANCE CURVE



COIL TEMPERATURE RISE



Relay Sockets

CE

c

UL

US

File No.: E253370

Features

- The dielectric strength can reach 5000VAC(I/O) and the insulation resistance is 1000MΩ
- Three mounting types are available: PCB, screw mounting and DIN rail mounting
- With finger protection device
- Many kinds of plug-in modules are available with the function of energizing indication and wiring protection
- Environmental friendly product (RoHS compliant)

CHARACTERISTICS

Type	Nominal Voltage	Nominal Current	Ambient Temperature	Dielectric Strength min.	Screw Torque	Wire Strip Length
14FF-1Z-A1	250VAC	10A	-40 °C to 70°C	5000VAC	—	—
14FF-1Z-C2	250VAC	10A	-40 °C to 70°C	5000VAC	0.6N·m	7mm
14FF-1Z-C3	250VAC	10A	-40 °C to 70°C	5000VAC	0.6N·m	7mm

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT




Unit: mm

Socket	Outline Dimensions	Wiring Diagram / PCB Layout	Components Available
<div>14FF-1Z-A1</div> <div></div> <div>PCB terminal, PCB or Screw mounting</div>	<div></div> <div>(Top View)</div>	<div></div> <div>(Top View)</div>	
<div>14FF-1Z-C2</div> <div></div> <div>Screw terminal, PCB or Screw mounting With finger protection device</div>	<div></div> <div>(Top View)</div>	<div></div> <div>(Top View)</div>	<div>plastic retainer 14FF-H5</div> <div>marker 14FF-M1</div> <div>jumper 14FF-J1</div> <div>plug-in module HFAA to HFHU*</div>
<div>14FF-1Z-C3</div> <div></div> <div>Screw terminal, DIN rail or Screw mounting With finger protection device</div>	<div></div> <div>(Top View)</div>	<div></div> <div>(Top View)</div>	<div>plastic retainer 14FF-H5</div> <div>marker 14FF-M1</div> <div>jumper 14FF-J1</div> <div>plug-in module HFAA to HFHU*</div>

Notes: \* Please refer to the product datasheet if plug-in module is required.

**DIMENSION OF RELATED COMPOENT (AVAILABLE)**

Unit: mm

**Retainer****14FF-H5 (Plastic retainer)****Marker****14FF-M1****Jumper****14FF-J1****Things to be noticed when selecting sockets:**

1. Please choose suitable relay socket according to the actual mounting environment, relay contact poles and terminal layout. If there is any query on selection, please contact Hongfa for the technical service.
2. Socket which can be mounted with markers is furnished with a marker; as for other related components, they should be selected separately. Please do give clear indication of the types of relay sockets and related components you choose while placing order.
3. The above is only an example of typical socket and related component type which is suitable to HF141FF relay. If you have any special requirements, please contact us.

**Disclaimer**

This datasheet is for the customers' reference. All the specifications are subject to change without notice.

We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.