


SDD SERIES SOLID STATE RELAY

SDD-060A002S-3
SDD-060A004S-3

DC Control DC Loading S.S.R



Specifications

MODEL SERIES NO.	CONTROL VOLTAGE	MUST TURN OFF VOLTAGE	INPUT IMPEDANCE	LOADING CURRENT	LOADING VOLTAGE	MIN BLOCKING VOLTAGE	MAX OFF-STATE LEAKAGE	FREQUENCY RANGE	MAX 1-CYCLE PEAK SURGE
SDD-060A002S-3	3-32 VDC	MAX 1.0 VDC	1.5 K Ω	2A	3- 60VDC	80VDC	LESS 2 mA	47-70HZ	3A
SDD-060A004S-3	3-32 VDC	MAX 1.0 VDC	1.5 K Ω	4A	3- 60VDC	80VDC	LESS 2 mA	47-70HZ	8.5A





MODEL SERIES NO.	MAX OFF STATE dv/dt	MAX ON-STATE VOLTAGE DROP	ISOLATE IMPEDENCE	DIELECTRIC STRENGTH INPUT-OUTPUT	DIELECTRIC STRENGTH INPUT/OUTPUT-CASE	TURN ON TIME	TURN OFF TIME	CAPACITANCE IN-OUT	WEIGHT (g)
SDD-060A002S-3	200 V/ μ sec	1.2Vrms	10 ⁹ Ω	2500 VACrms	—	LESS 2 msec	LESS 2 msec	LESS 15 PF	15 g
SDD-060A004S-3	200 V/ μ sec	1.2Vrms	10 ⁹ Ω	2500 VACrms	—	LESS 2 msec	LESS 2 msec	LESS 15 PF	15 g

Parts No.





SDD-060A002S-3

Packing : 3 = DIP Type
Phase : S = Single Phase
Loading Current : 002 = 2A, 004 = 4A
Control Voltage : A = 3-32VDC
Loading Voltage : 060 = 3~60VDC
Control Type : DD = DC Control DC
S = S.S.R


Outline Dimensions(Unit : mm)



Characteristic Curves



Equivalent Circuit



- 1.Input Circuit
- 2.Photo Detector
- 3.Amplifier
- 4.Protected Circuit