



8104 Концевой выключатель / выключатель путевой

Артикул: ME8104 / AE-8104 / KZ8104 / TZ8104 / AH8104 / AZ8104 / LJW8-8104 / YBLX-ME/8104



KZ-8104-AI - Концевой выключатель (усиленный) - ME-8104-AI

Артикул: ME8104 / AE-8104 / KZ8104 / TZ8104 / AH8104 / AZ8104 / LJW8-8104 / YBLX-ME/8104



8107 Концевой выключатель / выключатель путевой

Артикул: ME8107 / AE-8107 / KZ8107 / TZ8107 / AH8107 / AZ8107 / LJW8-8107 / YBLX-ME/8107



8108 Концевой выключатель / выключатель путевой

Артикул: ME8108 / AE-8108 / KZ8108 / TZ8108 / AH8108 / AZ8108 / LJW8-8108 / YBLX-ME/8108



KZ-8108-AI - Концевой выключатель (усиленный) - ME-8108-AI

Артикул: ME8108 / AE-8108 / KZ8108 / TZ8108 / AH8108 / AZ8108 / LJW8-8108 / YBLX-ME/8108



8111 Концевой выключатель / выключатель путевой

Артикул: ME8111 / AE-8111 / KZ8111 / TZ8111 / AH8111 / AZ8111 / LJW8-8111 / YBLX-ME/8111



8112 Концевой выключатель / выключатель путевой

Артикул: ME8112 / AE-8112 / KZ8112 / TZ8112 / AH8112 / AZ8112 / LJW8-8112 / YBLX-ME/8112



8122 Концевой выключатель / выключатель путевой

Артикул: ME8122 / AE-8122 / KZ8122 / TZ8122 / AH8122 / AZ8122 / LJW8-8122 / YBLX-ME/8122



8166 Концевой выключатель / выключатель путевой

Артикул: ME8166 / AE-8166 / KZ8166 / TZ8166 / AH8166 / AZ8166 / LJW8-8166 / YBLX-ME/8166

8169 Концевой выключатель / выключатель путевой



Артикул: ME8169 / AE-8169 / KZ8169 / TZ8169 / AH8169 / AZ8169 / LJW8-8169 / YBLX-ME/8169



ME-9101 Концевой выключатель / выключатель путевой KZ-8167 / TZ-8167
Артикул: ME9101 / AE-9101 / KZ8167 / TZ8167 / AH9101 / AZ8200 / LJW8-9101 / YBLX-ME/9101 / TZ-8167

рисунок, фотография, габаритные размеры чертёж смотрите ниже

KZ-8 Limit Switch



Предлагаем концевые выключатели(концевики) концевые выключатели KZ-8
ЭЛЕКТРОННЫЕ КОМПОНЕНТЫ РАЗЪЕМЫ (радиодетали) СО СКЛАДА И ПОД ЗАКАЗ
Беларусь г.Минск тел./факс 8(017)200-56-46 www.fotorele.net e:mail
minsk17@tut.by


Техническая информация продажа в Минске Беларусь datasheet pdf
техническая документация

описание фото рис. маркировка габариты размер параметры применение

Features

Double circuit type of limit switch Highly rigid construction, consists of intensive plastic and aluminum cast (Head and cover snugly fit in box)
Small volume, water-proof and oil-proof construction Built-in basic switch with double spring mechanism, longer mechanical life Smooth operation with greater OT Easy-to-wire circuit opening design Wide variety of actuators, easily use

Contact Form



Characteristics

Ratings

| Rated voltage | Noninductive Load (A) | | | | Inductive Load (A) | | | |
|---|--------------------------------|-------------------|-----------|------------|--------------------|----------|------------|----------|
| | Resistance Load | | Lamp Load | | Inductive Load | | Motor Load | |
| | NC | NO | NC | NO | NC | NO | NC | NO |
| 125VA C 250VA C 500VA C | 5.5 | 5.5 | 1.5 1 | 0.7 0.5 | 3.3 | 3.3 | 2 1.5 | 1 0.8 |
| 8VDC 14VDC 30VDC 125VDC 250VDC C | 5.5 0.4 0.2 | 5.5 0.4 0.2 | 3.3 3 | 3.3 3 | 5.4 4 | 4.4 4 | 3.3 3 | 3.3 3 |
| Inrush Current | N.C: below 24A, N.O: below 12A | | | | | | | |

| | |
|---|--|
| Operation speed | 0.5mm-50cm/sec |
| Operating frequency Contact resistance | Mechanical: 120 operations/minute Electrical: 30 operations/minute 25m max. (initial value) |
| Insulation resistance | 100m min. at 500VDC |
| Dielectric strength | 1000VAC, 50/60 HZ for 1 minute between terminals of the same polarity 1500VAC, 50/60 HZ for 1 minute between each terminal and ground |
| Vibration | 10-55HZ, 1.5mm double amplitude |
| Shock | Mechanical durable: 1,000m/Sec ² (about 100G'S) Malfunction: 300m/Sec ² (about 30G'S) |
| Ambient temperature | -5 to +65 |
| Humidity | <95% RH |
| Life | Mechanical: 10,000,000 operations above Electrical: 500,000 operations above |
| Weight | About 130 to 190g |
| Degree of protection | IP65 |

Operating characteristics

| Models | KZ-8104 | KZ-8108 | KZ-8107 | KZ-8111 | KZ-8112/8122 | KZ-8166/8167/8168/8169 |
|---------|---------|---------|---------|----------|--------------|------------------------|
| OF Max. | 750g | 750g | 750g | 900g | 900g | 150g |
| RF Min. | 100g | 100g | 100g | 150g | 150g | - |
| PT Max. | 20 | 20 | 20 | 1.5mm | 1.5mm | 30mm |
| OT Min. | 50 | 50 | 50 | 4mm | 4mm | - |
| MD Max. | 12 | 12 | 12 | 1mm | 1mm | - |
| OP | - | - | - | 26 0.8mm | 37 0.8mm | - |

KZ-8 Limit Switch

Appearance and dimension

